

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
14 July 2005 (14.07.2005)

PCT

(10) International Publication Number  
**WO 2005/064375 A1**

(51) International Patent Classification<sup>7</sup>: **G02B 6/293**,  
G02F 1/01

(21) International Application Number:  
PCT/EP2003/014918

(22) International Filing Date:  
24 December 2003 (24.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): **PIRELLI & C. S.P.A.** [IT/IT]; Via Gaetano Negri, 10, I-20123 Milano (IT).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **FACCIO, Daniele, Franco, Angelo** [IT/IT]; Pirelli Labs S.p.A., Viale Sarca, 222, I-20126 Milano (IT). **ROMAGNOLI, Marco** [IT/IT]; Pirelli Labs, Viale Sarca, 222, I-20126 Milano (IT).

(74) Agents: **MONTEVECCHI, Emma** et al.; Cantaluppi & Partners S.r.l., Via Matteotti, 26, I-35137 Padova (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

— *as to the identity of the inventor (Rule 4.17(i)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL,*

[Continued on next page]

(54) Title: LOW LOSS MICRORING RESONATOR DEVICE



(57) Abstract: It is disclosed a low loss micro-ring resonator device (10; 100; 10') which comprises a closed-loop resonator waveguide (2) having a first refractive index ( $n_r$ ), the resonator waveguide (2) defining an inner (16) and an outer region (17) by an outer curved edge (15) of the waveguide (2). The resonator waveguide is arranged on a substrate (6; 6') having a second refractive index ( $n_b$ ), the refractive index difference ( $\Delta n_1$ ) between the first refractive index ( $n_r$ ) and the second refractive index ( $n_b$ ) is greater than 0.3. The device (10) also comprises an upper cladding (20) covering the inner region (16) of the resonator waveguide (2) having a third refractive index ( $n_{uc}$ ); and a lateral cladding (21) in contact with the outer curved edge (15) and extending in the outer region (17), said lateral cladding (21) having a fourth refractive index ( $n_{lc}$ ), the fourth refractive index ( $n_{lc}$ ) being lower than said third refractive index ( $n_{uc}$ ). A method for reducing propagation losses of a resonator device (10; 100; 10') is also described.

WO 2005/064375 A1



SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

**Published:**

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.